

FLOAT SWITCH

- **Economical mains water top-up**
- **Switching cycle of only 9 cm**
- **Quick and easy to attach to submersible pump**



Quickly to install:

Float switches can be safely fitted to the pump housing of the Multigo submersible pressure pump!



Float switch for mains water top-up (yellow)

Item No.

Float switch for controlling top-up with mains water. For attachment to the inlet pipe or the submersible pump. The switch lever defines the switching points so precisely that the water level rises by only 9 cm (daily requirement for single-family home). Switch lever and retaining clamp (for pipe diameter of 110 – 130 mm / 4 – 5 in.) made of stainless steel. Float housing (yellow), butt-spliced, made of polypropylene. With flexible connecting cable 3 x 1 mm². *(without adapter plug).*

Components/spare parts

Item No.

- | | |
|---|---------|
| ▶ with 3 m (9.8 ft.) connecting cable | SS 1001 |
| ▶ with 10 m (32.8 ft.) connecting cable | SS 1002 |
| ▶ with 15 m (49.2 ft.) connecting cable | SS 1041 |
| ▶ with 20 m (65.6 ft.) connecting cable | SS 1003 |

Components/spare parts

Item No.

Float switch (*mains top-up*),
without switch lever and clamp

- | | |
|---|---------|
| ▶ with 3 m (9.8 ft.) connecting cable | SS 1021 |
| ▶ with 10 m (32.8 ft.) connecting cable | SS 1022 |
| ▶ with 20 m (65.6 ft.) connecting cable | SS 1023 |

Float switch for dry run protection (red)

Item No.

Float switch to turn off pump when water level in tank is too low. For attachment to the inlet pipe or the submersible pump. When the water level in the tank reaches the minimum required level again, the pump is released for operation again by the float switch. With switch lever for precise definition of switching points, only 9 cm (1.6 in.) switching cycle. Switch lever and retaining clamp (for pipe diameter of 110 – 130 mm / 4 – 5 in.) made of stainless steel. Float housing (red), butt-spliced, made of polypropylene. With flexible connecting cable 3 x 1 mm². *(without adapter plug).*

Components/spare parts

Item No.

- | | |
|---|---------|
| ▶ with 3 m (9.8 ft.) connecting cable | SS 1011 |
| ▶ with 10 m (32.8 ft.) connecting cable | SS 1012 |
| ▶ with 20 m (65.6 ft.) connecting cable | SS 1013 |

Components/spare parts

Item No.

Float switch (*dry run protection*),
without switch lever and clamp

- | | |
|---|---------|
| ▶ with 3 m (9.8 ft.) connecting cable | SS 1031 |
| ▶ with 10 m (32.8 ft.) connecting cable | SS 1032 |
| ▶ with 20 m (65.6 ft.) connecting cable | SS 1033 |

Accessories

Item No.

- | | |
|---|---------|
| ▶ Adapter plug for connection of float switch control cable | SS 0149 |
|---|---------|

