

SECTIONAL GRP TANKS

- Made in the UK to BS EN13280 by reputable manufacturer
- Available in a huge range of sizes from 1000 litres
- Factory insulated hot press panels - HCFC & CFC free
- Can be supplied with valve housings c/w inlet valve
- Mains water connections by type AA or AB air gap
- Internally or externally flanged options
- Condensation trays available
- Inlets and outlets fitted to suit your requirements.



Sectional pre-insulated water tanks any size from 1000 litres upwards. GRP sandwich construction manufactured under ISO 9001:2008 and either internally or externally flanged.

Suitable for storage of rainwater (or mains cold water) where the tank must be above ground, either indoors or outdoors. Tanks can be supplied in virtually any capacity to customers' requirements, with internal divisions, top or side access and finished in any RAL colour as required.

Professional Installation

All sectional tanks are built to approved drawings and include on-site installation by professional certified contractors.



For more information, sizes, dimensions etc. please call.

01452 772000



RAINHARVESTING SYSTEMS



Commercial Rainwater Harvesting

- Schools
- Offices
- Industrial
- Agriculture
- Horticulture
- Vehicle wash

Flexible System Design

Our comprehensive RainTech® range of specialist products has been developed specifically for use in Rainwater Harvesting Systems. Because the range consists of separate components, it has exceptional flexibility.

This enables us to design a system for almost any application. With years of experience and our in-depth product knowledge, we can provide the right solution to suit your requirements.



We are the UK's sole supplier of Wisy® products for rainwater utilisation

PRE-INSULATED SECTIONAL TANKS

Tank panels are available in metric or imperial sizes, giving a wide range of different formats, up to 4m in height.

Each tank we supply is configured to suit requirements, with inlets, outlets, overflow etc. sized to suit demand.

Standard tanks are supplied with 25mm insulation and 50mm or 75mm thick versions are also available. Tanks greater than 1.5m high can be supplied with internal and external ladders, and safety railings where required.

In addition to standard rainwater storage tanks, we can supply any tank configured as a Category 5 break tank specifically for use in rainwater harvesting. Such tanks will be pre-fitted with calmed inlets and backflow protection for mains water in compliance with Water Regulations.



Internal and external ladders can be supplied as required



Raised valve housing with screened weir overflow giving a type AB air gap, can be fitted with drop-arm equilibrium float valve or Keraflo valve where required.



*Keraflo
Aylesbury valve
type KB*

Mains water inlets can either have a type AA air gap arrangement using a tundish, or type AB using a raised valve housing with weir overflow. For type AA tanks we can supply solenoid valve / tundish assemblies, and for type AB we can supply either Keraflo or drop-arm equilibrium float valves.

Tanks can also be supplied with a tundish and solenoid arrangement to provide a type AA air gap.

The tundish contains a laminar flow device for splash-free filling.



*RainTech® mains
water top-up unit*



Distributor:

Rainharvesting Systems Ltd.

Calf Way, Bisley,
Stroud,
Gloucestershire GL6 7BX

Tel: 01452 772000

Fax: 01452 772008

E-mail: sales@rainharvesting.co.uk

Website: www.rainharvesting.co.uk

NB continuous development may necessitate change in these details without notice E&OE.

Data Sheet DW/15/02